

**LASOS<sup>®</sup>** **DPSS laser series**

Diode-pumped solid-state laser  
**50 mW output at 607 nm**



**RLK 0750 TS**

- Single frequency
- Outstanding long term stability
- Excellent beam quality
- Reliable and robust
- Maintenance free
- Compact design
- Suitable for OEM applications
- Customization on request



## Diode-pumped solid-state laser

### Specifications RLK series:

#### LASOS® DPSS laser series

The LASOS® DPSS laser series provide excellent beam quality in a variety of wavelengths based on the latest progress in solid state laser technology.

The LASOS® DPSS laser series offers a reliable and compact single frequency laser source in the VIS.

The LASOS® DPSS laser series provide the ideal products for applications in:

- Spectroscopy
- Interferometry
- Confocal and fluorescence microscopy
- Bioanalytical research
- Particle measurements
- Metrology
- Industrial measurements
- Medical
- Science and education



Customized solutions for specific applications are possible

Wavelength	607 nm ± 0.5 nm
Wavelength stability (8 h)	± 5 pm
Spectral Linewidth <sup>1</sup>	< 1 MHz
Output power	50 mW
Output power stability within 8 h	< ± 2 %
Noise 30 Hz ... 10 MHz	≤ 2 % rms
Warm up period	≤ 10 min
Transversal mode M <sup>2</sup>	≤ 1.1
Beam waist diameter (1/e <sup>2</sup> )	0.7 mm ± 0,07 mm
Beam ellipticity	1 ± 0,15
Pointing stability	< 6 μrad K <sup>-1</sup>
Beam divergence	≤ 1.4 mrad
Polarization ratio	≥ 200:1
Controller	CKL 2405, CKL 1005







<sup>1</sup>Allan Deviation for sample period < 0.5 s

Options on request

Dimensions [mm]:  
Laser Head



Controller  
(CKL 2405/CKL 1005)



# LASOS

For worldwide photonics

LASOS Lasertechnik GmbH  
Franz-Loewen-Str. 2  
07745 Jena  
Germany

Phone: +49 (0) 3641 2944 – 0  
Fax: +49 (0) 3641 2944 – 300  
sales@lasos.com

[www.lasos.com](http://www.lasos.com)